Pilot Lamp Data (Cont'd)

Lamp No.	Bead Color	Base (Miniature)	Bulb Type	Rating Volts	Rating Amps.	Used For
PR-2	Blue	Flange	B-3½	2.4	0.50	Flashlights
PR-3	Green	Flange	B-3½	3.6	0.50	Flashlights
PR-4	Yellow	Flange	B-3½	2.3	0.27	Flashlights
PR-6	Brown	Flange	B-3½	2.5	0.30	Flashlights
PR-12	White	Flange	B-3½	5.95	0.50	Flashlights
12	.....	2-Pin	G-3½	6.3	0.15	Dials
40	Brown	Screw	T-3¼	6-8	0.15	Dials
41	White	Screw	T-3¼	2.5	0.5	Dials
42	Green	Screw	T-3¼	3.2	‡	Dials
43	White	Bayonet	T-3¼	2.5	0.5	Dials and Tuning Meters
44	Blue	Bayonet	T-3¼	6-8	0.25	Dials and Tuning Meters
45	*	Bayonet	T-3¼	3.2	‡	Dials
46▲	Blue	Screw	T-3¼	6-8	0.25	Dials and Tuning Meters
47	Brown	Bayonet	T-3¼	6-9	0.15	Dials
48	Pink	Screw	T-3¼	2.0	0.06	Battery Set Dials
49	Pink	Bayonet	T-3¼	2.0	0.06	Battery Set Dials
50	White	Screw	G-3½	6-8	0.2	Auto-Radio Dials; Flashlights
51▲	White	Bayonet	G-3½	6-8	0.2	Auto-Radio Dials; Panel Boards
55	White	Bayonet	G-4½	6-8	0.4	Auto-Radio Dials; Parking Lights
57	White	Bayonet	G-4½	14	0.24	Auto Radio Dials
112	Pink	Screw	TL-3	1.1	0.22	Flashlights
222	White	Screw	TL-3	2.2	0.25	Flashlights; Soldering Guns
1458	.....	Bayonet	G-5	20.0	0.25	Dials
1490	White	Bayonet	T-3¼	3.2	0.15	Dials
1891	Pink	Bayonet	T-3½	14	0.23	Auto Radio Dials
1892	White	Screw	T-3½	14	0.12	Auto Panel Lights

*White in G.E. and Sylvania; Green in National Union Raytheon and Tung-Sol.
‡0.35 in G.E. and Sylvania; 0.5 in National Union Raytheon and Tung-Sol.
▲Have frosted bulb.

Neon Glow Lamps

High Brightness

Lamp Number	Hours of Average Useful Life*	Maximum Overall Length	Base	Nominal Current in Ma.	Circuit Volts, AC or DC	Nominal Watts 110-125 V.
NE-2H	25,000	¾"	2" Wire Term.	1.7	110-125	1/5
NE-2J	25,000	1⅝"	S.C. Mid. Flange	1.7	110-125	1/5
NE-2P	25,000	¾"	1" Wire Term.	1.7	110-125	1/5
NE-51H	25,000	1¼"	Min. Bay.	1.2	110-125	1/7

Standard Brightness

NE-2	25,000	1⅛"	1" Wire Term.	0.5	110-125	1/17
NE-2D	25,000	1⅝"	S.C. Mid. Flange	0.6	110-125	1/15
NE-2E	25,000	¾"	2" Wire Term.	0.6	110-125	1/15
NE-2M	25,000	¾"	1" Wire Term.	0.5	110-125	1/17
NE-7	7,500	1¼"	1⅛" Wire Term.	2.0	110-125	¼
NE-17	7,500	1½"	D.C. Bay	2.0	110-125	¼
NE-21	7,500	1½"	S.C. Bay	2.0	110-125	¼
NE-30	10,000	2¼"	Med. Screw	12.0	110-125	1
NE-34	10,000	3½"	Med. Screw	18.0	110-125	2
NE-42	10,000	3¹³⁄₁₆"	D.C. Bay	30.0	110-125	3
NE-45	7,500	1¹⁷⁄₃₂"	Cand. Screw	2.0	110-125	¼
NE-48	7,500	1½"	D.C. Bay	2.0	110-125	¼
NE-51	15,000	1¾"	Min. Bay	0.3	110-125	1/25
NE-56	10,000	2¼"	Med. Screw	5.0	220-250	1
NE-57	7,500	1¹⁷⁄₃₂"	Cand. Screw	2.0	110-125	¼
NE-58	7,500	1¹⁷⁄₃₂"	Cand. Screw	2.0	220-250	½
NE-79	10,000	2"	D.C. Bay	12.0	110-125	1

Argon Glow Lamps

AR-1	1,000	3½"	Med. Screw	18.0	110-125	2
AR-3	150	1¹⁷⁄₃₂"	Cand. Screw	3.5	110-125	¼
AR-4	150	1½"	D.C. Bay	3.5	110-125	¼
AR-9	50	1¼"	1" Wire Term.	0.3	110-125	1/25

*On A.C. unless otherwise noted. D-C life is approximately 60% of A-C values.